

China MINKO

VPC-62-32AC

negotiation

L210xW85xH52 (mm)

1000000 pieces per month

8 -10 working days

7Kw 32A Home EV Fast Charger Type2 Portable Charger For Electric Vehicles

CE(ICR lab), UKCA, ROHS, ISO, REACH

MoneyGram, Paypal, Skrill, Transferwise

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 5 pieces
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms: T/T, Western Union,
- Supply Ability:



Product Specification

Highlight:	250vac home fast charger for tesla,
• Electric Cable:	IP65 Circuit Breaker
• Start Method:	Plug And Play
Operating Temperature:	-35°C To 50°C
 Input Power: 	250V Max
Rated Power:	7kW
Rated Current:	32A
 Rated Voltage: 	AC 200-250V
Charging Plug:	IEC 62196 Type 2

32a tesla fast charger for home, 7kw tesla fast charger for home



More Images



7Kw 32A Home EV Fast Charger Type2 Portable Charger For Electric Vehicles

Detailed specification:

Portable EV Charger, with power ratings of 3.5KW, 7 kW, is suitable for different types of vehicles. Adjustable current, suitable for various scenarios.

The Voltage and Current are stable during charging, which can protect the battery and delay using time.

We can use normally in ultra-high temperature environment up to 50 °C.

It can also be used normally in the -35°C.

Model No. VP Rated voltage AC Rated current 32/ Rated power 7kl Certificates CE	
Rated voltageACRated current32/Rated power7klCertificatesCE	C 200-250V 2A W E(ICR Iab), UKCA, ROHS,ISO, REACH
Rated current32/Rated power7kVCertificatesCE	2A W E(ICR Iab), UKCA, ROHS,ISO, REACH
Rated power 7kV Certificates CE	W E(ICR lab), UKCA, ROHS,ISO, REACH
Certificates CE	E(ICR lab), UKCA, ROHS,ISO, REACH
Protection rank IP5	54 cable; IP65 circuit breaker
electric cable	65 circuit breaker
LCD 2.8	8" LCD screen
LED indicator Blu	ue/Red/Green
Earth leakage 30r protector)m AC
input power 250	50V Max
length 5m	n or customized
Package Size L2 ⁻	210xW85xH52 (mm)
	ug and Play
Operating temperature -35	5°C to 50°C
electrical protection Ov	vercurrent protection, residual current protection, grounding protection, surge protection, vervoltage/undervoltage protection, overvoltage/underfrequency protection, overtemperature otection
Applied Materials Ca	ousing: Black thermoplastic PC940. Corrosion and wear protection. able: 4.5M black with TPU jacket. ith CE and TUV mark issued by TUV.
2.II Feature 3. (3. (The product complies with the Low Voltage Directive 2014/35/EU, IEC61851-1:2019 IP67, weatherproof; leakage protection; impact resistance Charging status and working error are simply displayed by LED indicator light and LCD screen Optional function of current selection button, 8A-32A free switching current
Warranty 1 Y	Years for the whole machine

Advanteages:

Temperature Protection Efficient Charging Short Circult Protection Protection Level IP66 Built in Smart Chip



rotection

4

Efficient Charging Short Circuit Protection

Protection Level IP66 S

Built in Smart Chip

Product details





Customizable plug



Customizable







Simple and easy to operate



EV CHARGING



Easy to carry and charge



Packing list

Packing list





Caution:

Don't submerge the EV charging cable in water.

Don't step on, fold or knot the cable.

Don't drop the EV charging box or place a heavy object on it.

Don't place the charging cable near high temperature object when charging.

Don't operate the EVSE in temperatures beyond its operating range of -25°C to 55°C.

Power-supply side input cable should be at least 3*2.5mm (recommended 3*4mm), with a standard 16A socket. It is suggested that

the power distribution is done by the professionals.

Don't put fingers into the charging connector when the power plug is still connecting to the power.

Don't use this EV charging box when the cable is damaged.

The EV charging box is only for EV charging using.

Don't use this device with other brand's extension cord or adapter.

